



DIGITAL HOTPLATE STIRRERS

Digital Hotplate Stirrers are ideal for general lab applications such as mixing reagents and stirring bacteriological cultures. Constructed of anodized high grade aluminum alloy (MS-01HA) or white glass ceramic (MS-01H7A And MS-01H10A) ensures these units are durable and highly resistant to corrosion. The aluminum body and brushless motor provide maintenance free operation.



MS-01H7A
Ceramic Digital Hot-Plate Stirrer



MS-01HA
Digital Hot-Plate Stirrer



MS-01H10A
Large Capacity Digital
Hotplate Stirrer

PRODUCT FEATURES:

- Fast heat time is less than 8 minutes for plates to rise from ambient to 300°C
- Brushless DC motor provides accurate stirring speed and maintenance free operation
- These plates have strong magnets to prevent loss of stirring speed.
- When the plate is hot during operation a warning light flashes
- Automatic shut-off if plate's temperature exceeds model limits or shows no temperature rise after 30 seconds of heating
- External temperature probe connector



For over 25 years Crystal Technology and Industries has been driven to deliver exceptional value to the scientific marketplace by developing innovative equipment and Cryo Storage Solutions for today's scientist.

jdmlabsolutions.com | jim@jdmlabsolutions.com | 724-413-0076



Digital HotPlate Stirrers

Fast even heating with strong magnets that provide superior results

Specifications

Model	MS-01HA	MS-01H7A	MS-01H10A
Product Name	Digital Hotplate Stirrer	Ceramic Digital Hotplate Stirrer	Large Capacity Digital Hotplate Stirrer
Speed	0, 80~1500 RPM		
Speed Resolution	10 RPM		
Plate Temperature	Ambient ~ 300°C	Ambient ~ 540°C	
Temperature Accuracy	@100°C: ≤±10°C		
Temperature Stability	@100°C: ≤±5°C		
Temperature Resolution	0.1°C		
Safety Shut Off Temperature	360°C	580°C	
Max Stirrer Bar Length	80 mm (3.1 in)		
Platform Size	175 x 175 mm (6.9 x 6.9 in)		254 x 254 mm (10 x 10 in)
Capacity	10L		20L
Platform Material	Aluminum	Ceramic	
Number of Stirring Postions	1		
Accessory Included in Standard Packaging	MSA15 Stirrer Bar Ø12x50 mm (Ø0.47 x 1.97 in)		
Display	LCD		
Operating Environment	Ambient Temperature: 5°C~40°C		
	Relative Humidity: ≤80%		
Power Supply	AC110V±11V, 60Hz		
Max Power Consumption	1000W		1500W
Dimensions WxDxH	240 x 355 x129 mm (9.5 x 14.0 x 5.1 in)		299 x 442 x 152 mm (11.8 x 17.4 x 6.0 in)
Net Weight	4.5 kg (9.9 lb)		6.9 kg (15.2 lb)
IP Protection Rating	IP21		